



Technical Data Sheet

Rytons EavesGuard®



Dimensional Drawing



In-Situ Line Drawing



In-Situ Drawing



Main Uses, Features and Benefits

- Felt support and felt replacement system.
- U.V. stabilised against deterioration by sunlight.
- Eliminates roof felt sagging at rear of fascia.
- Eliminates felt rot at gutter level.
- Compatible with Rytons over fascia vents and RytComb.



H60 Plain Roof Tiling

Specification Clause 355

H61 Fibre Cement Slating

H62 Natural Slating

H65 Single Lap Roof Tiling

Specification Clauses 47, 355



Product Specification Code

Rytons EG920.

Size

920mm (L) x 307mm (D).

R14 AutoCAD drawing available by e-mail.

Free Area

Not applicable.

Composition

U.V. stabilised high impact polystyrene.

Colours

Black.

Specification Paragraph

Manufacturer:

Rytons Building Products Ltd Tel: 01536 511874 Fax: 01536 310455

Email: admin@rytons.com Web: www.vents.co.uk (updated regularly)

Product ref: Rytons EavesGuard® Black (ref EG920)

Installation

Fix through the EavesGuard® to the top of the fascia board and/or to the rafters. A 10mm interlocking overlap at each end promotes quick and easy installation and ensures correct positioning and a neat aligned appearance.

Handling Information

Box quantity: 50 lengths.

Box size: 96cm (W) x 11cm (H) x 32cm (D).

Box weight: 5.5kg.

Technical Data Sheet

Rytons EavesGuard®

Photo Library



On Site

Previously manufactured in clear. Now U.V. stabilised black.



Questions

Will the EavesGuard® rattle when fitted?

All felt support or felt replacement systems may occasionally 'rattle' in severe conditions although this would obviously depend on how and where they were fitted, and the direction and force of wind to which they may be subjected.



Please recycle printouts where facilities exist.