

Technical Data Sheet

Rytons Mixed Boxes of Louvre Ventilators



Irish Reg. Stat.



Mixed Box of Rytons Louvre Ventilators (Without Flyscreens)


Main Uses, Features and Benefits

- 32no of Rytons popular louvres.
- Room and cupboard ventilators.
- Low profile fixed open louvres.
- High air flows.
- For internal and external use.
- Embossed with DO NOT BLOCK.
- U.V. stabilised for internal and external use.
- All vents individually bagged for display.
- 7no '9x3' (LV88BG).
- 18no '9x6' (LV177BG).
- 7no '9x9' (LV265BG).




Rytons Louvre Ventilator '9x3' (LV88)

7 Number




Rytons Louvre Ventilator '9x6' (LV177)

18 Number



Rytons Louvre Ventilator '9x9' (LV265)

7 Number



Product Specification Code

Rytons LVMIXWH.

Size

LV88: 271mm (L) x 95mm (H).

LV177: 271mm (L) x 171mm (H).

LV265: 271mm (L) x 247mm (H).

R14 AutoCAD drawings available by e-mail.

Free Area

LV88: 8800mm² (88cm²) (13½"²) per unit.

LV177: 17760mm² (177.6cm²) (27½"²) per unit.

LV265: 26500mm² (265cm²) (41"²) per unit.

Composition

U.V. stabilised high impact polystyrene.

Colours

White.

Installation

Position over opening and fasten into place.

BBA Approval

Rytons has **73** British Board of Agrément approved products; the largest range on the market. BBA certification is third party evaluation and accreditation, and approved products are accepted by building control officers, architects, engineers and surveyors nationwide. The NHBC also accept products approved by the BBA when used as stated in the relevant BBA certificate. Rytons also has an Irish Building Regulation Statement for each of their three BBA certificates.

Handling Information

Box quantity: 32 number.

Box weight: 3.20kg.



Please recycle printouts where facilities exist.



Technical Data Sheet

Rytons Mixed Boxes of Louvre Ventilators



Mixed Box of Rytons Louvre Ventilators (With Flyscreens)

Main Uses, Features and Benefits

- 32no of Rytons popular flyscreened louvres.
- Room and cupboard ventilators.
- Low profile fixed open louvres.
- High air flows.
- For internal and external use.
- Embossed with **DO NOT BLOCK**.
- All vents individually bagged for display.
- U.V. stabilised for internal and external use.
- 7no '9x3' (LV68FBG).
- 18no '9x6' (LV137FBG).
- 7no '9x9' (LV205FBG).



Product Specification Code

Rytons LVFMIXWH.

Size

LV68F: 271mm (L) x 95mm (H).

LV137F: 271mm (L) x 171mm (H).

LV205F: 271mm (L) x 247mm (H).

R14 AutoCAD drawings available by e-mail.

Free Area

LV68F: 6600mm² (66cm²) (10"²) per unit.

LV137F: 13300mm² (133cm²) (20½"²) per unit.

LV205F: 20000mm² (200cm²) (31"²) per unit.

Composition

U.V. stabilised high impact polystyrene.

Colours

White.

Installation

Position over opening and fasten into place.

BBA Approval

Rytons has 73 British Board of Agrément approved products; the largest range on the market. BBA certification is third party evaluation and accreditation, and approved products are accepted by building control officers, architects, engineers and surveyors nationwide. The NHBC also accept products approved by the BBA when used as stated in the relevant BBA certificate. Rytons also has an Irish Building Regulation Statement for each of their three BBA certificates.

Important Note

Rytons Flyscreened Louvre Ventilators may not be used to ventilate a heat producing appliance because they incorporate a flyscreen.


Handling Information

Box quantity: 32 number.

Box weight: 4.58kg.


Rytons Louvre Ventilator with Flyscreen '9x3' (LV68F)

7 Number




Rytons Louvre Ventilator with Flyscreen '9x6' (LV137F)

18 Number



Rytons Louvre Ventilator with Flyscreen '9x9' (LV205F)

7 Number



Please recycle printouts where facilities exist.